

H.264 DVR Kit

D7724HT & C7834SC x4



Key Features

- H.264 Compression & Virus free Linux O/S
- 4-channel real time playback at the same time
- User-friendly interface: 16 bit true color, semi-transparent graphical user interface
- Support D1, HD1, CIF for recording quality
- Fluent internet transmission
- Support USB DVD backup
- Power to 4 cameras is from DVR
- Suitable for fields as supermarkets, chain stores, community security or villa
- Hi-speed backup/upgrade/record via USB2.0

DVR Specifications

Image Compression	H.264
System	NTSC/PAL
Video Input	4 channels 1.0Vp-p 75ΩBNC
Video Output	2 channels 1.0Vp-p 75Ω BNC
Audio Input	4channels 1.0Vp-p 75Ω RCA
Audio Output	1channels 1.0Vp-p 75Ω RCA
Audio Compression	ADPCM
Recording Frame Rate	100fps for CIF
Recording Resolution	NTSC: 30/720x480; 60/720x240; 120/360x240 PAL: 25/720x576; 50/720x288; 100/360x288
Video Display	D1 pixels, 1/4 display
Video Playback	Supports 4 channels playback at the same time
HDD Capacity	1 SATA, Supports up to 1 TB
USB Interface	1PCS USB2.0 for backup; 1PCS USB1.1 for mouse
Motion Detection	Zone setup: PAL: 13 x 10(130) NTSC: 13 x 8(104)
Serial Interface	RS-485
Network Interface	RJ-45, 10M/100M
Power Source	DC 19V/3A
Power Consumption	60W
Mobile Monitoring	Support GPRS/CDMA/EDGE/3G
VGA Interface	Yes
Alarm In	4
Alarm Out	1
Operating Temperature	0~50°C
Dimensions (W×L×H)	300mm x 250mm x 60mm

Camera Specifications

Image Sensor	1/4" Sony Super HAD CCD
Signal System	PAL/NTSC
Horizontal Resolution	420TV Line
Lens	3.6mm
Night-Vision Range	15m
Minimum Illumination	0Lux (IR on)
Video Output	1.0Vp-p, 75Ω (BNC)
Auto Iris	
Electronic shutter	1/50 (1/60) - 1/100,000(s)
Gain Control	Auto
Effective Pixels	PAL: 500 (H)×582(V) NTSC: 510(H)×492(V)
White Balance	Auto
Gamma Correction	
Back light compensation	Auto
S/N Ratio	More than 48db (AGC OFF)
Power Consumption	
Power Supply	DC12V/140mA, 300mA(IR on)
Housing	
Operation Temperature	-10°C~50°C
Dimension	1.0Vp-p, 75Ω (BNC)
Weight	
Weatherproof	IP66

H.264 DVR Kit

SRP £399.95